

global accord seating | product specification

Pedestal Base Chairs

Models: 2670-4PB, 2671-4PB, 2676-4PB, 2677-4PB

Dimensions

| | | |
|------------------------|--------------------|---|
| Overall Depth | | 25 in / 635mm |
| Overall Width | | 25 in / 635mm |
| Overall Height | | 39.5-41.5 in / 1003-1054mm |
| | 2670-4PB, 2676-4PB | 34.5-36.5 in / 876-927mm |
| | 2671-4PB, 2677-4PB | 876-927mm |
| Seat Depth | | 19 in / 483mm |
| Seat Width | | 20 in / 508mm |
| Seat Height | | 16.5 - 18.5 in / 419-470mm |
| Back Height | 2670-4PB, 2676-4PB | 23 in / 584mm |
| | 2671-4PB, 2677-4PB | 18 in / 457mm |
| Armrest Clearance | | 20 in / 508mm |
| Arm Height - From Seat | | 8.5 in / 216mm |
| Product Weight | 2670-4PB, 2676-4PB | 39 lb / 17.7 kg |
| | 2671-4PB, 2677-4PB | 36 lb / 16.4 kg |
| Shipment Weight | 2670-4PB, 2676-4PB | 47 lb / 21.4 kg |
| | 2671-4PB, 2677-4PB | 44 lb / 20.0 kg |
| Shipping Cube | | 10.75 ft ³ / 0.30 m ³ |

Contact sales representative for more information.

Features

- Elasticized breathable mesh back or pleated back upholstery detail
- Front edge of seat is a seamless waterfall
- Pedestal base secures chair to the floor while allowing chairs to swivel
- Mechanism provides 2 in (51mm) pneumatic seat height adjustment, tilt lock and adjustable tilt tension
- Soft decent pneumatic cylinder with automatic return to maximum height and return to center
- Fixed height, polished aluminium arms

Options

- Cylinders that do not automatically return to center or do not swivel at all, are available. These optional cylinders automatically return to center

MODELS: 2676-4PB, 2677-4PB

- 24 standard mesh colors are available from the Vue mesh program
- Matching Program offers 12 colors, available for mesh back and matching seat

Construction (Arms)

- Cast aluminum arms
- Arms are bolted with steel-on-steel connectors into seat deck on underside on chair
- Hardware on underside of arms is accessible for removing/attaching armcaps
- Self-skinned urethane (SSU) armcaps
- All armcaps are field replaceable



2670-4PB



2671-4PBt



2676-4PB



2677-4PB



global accord seating | product specification

Construction (Seat and Back)

- Plywood seat pan, 0.5 in (13 mm) thick, 8-ply
- Tubular steel back frame

Construction (Base)

- Metal base plate with black metal cover and black cylinder cover
- See installation guide (available on our installation guide web page)
- Base plate mounts to floor. Mounting hardware not included

Construction (Mechanism)

- Constructed of cast aluminum and stamped steel
- Connected to gas-assisted pneumatic cylinder

Upholstery

- Seat can be upholstered in fabric, vinyl or leather
MODELS: 2676-4PB, 2677-4PB
- Elastomeric mesh back
MODELS: 2670-4PB, 2671-4PB
- Fully upholstered pleated back cover
- Seat and back can be upholstered in fabric, vinyl, leather or leather/mock leather combination

Foam (Seat)

- High density Ultracell foam. Density 1.8 lb
- Dual-foam layers:
 - 1.25 in (32 mm) thick layer, ILD: 32
 - 1.75 in (45 mm) thick layer, ILD: 50

Weight Capacity

Designed for an active weight capacity of 300 lb

Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foam and textiles
- 12 year warranty on control mechanisms
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating

All foam and textiles are tested and certified, meeting California Technical Bulletin 117 (CAL TB 117-2013) standards.

Environmental

View [Environmental Data Sheets](#) online. All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications.

