

primacare seating | product specification

Metal Frame Dining Seating Model GC3616

Dimensions

Overall Depth		23 in / 584 mm
Overall Width		23 in / 584 mm
Overall Height		34.5 in / 876 mm
Seat Depth		17.5 in / 445 mm
Seat Height		18 in / 457 mm
Armrest Clearance		19 in / 483 mm
Arm Height - From Seat		8.5 in / 216 mm
Back Height - From Seat		16.5 in / 419 mm
Product Weight	GC3616	50 lbs / 22.7 kgs
	GC3616CA	58 lbs / 26.4 kgs
Shipping Cube		13.25 ft ³ / 0.37 m ³

Contact sales representative for more information.

Features

- Wall saver leg design prevents chair back from contact with wall
- Integrated lumbar support
- Standard Self-Skinned Urethane (SSU) armcaps
- Complementing tables are available
- Shipped fully assembled

Options

- Rear casters are available for easy relocation of chair. Also available with lift mechanism foot pedal, allowing caregiver to gently move a seated person to and from a table
- Under arm space is open, as standard, but closed arms are available for all models in matching upholstery (CA models)
- Seven frame finishes are available
- SSU armcaps are available in several colours
- Optional wood armcaps are available in any standard GLOBALcare wood finish

COM Yardage

Yardage is based on unmatched materials with widths of 54 inches for seating

MODEL GC3616

- Full Unit: 1.50 yards
- Back: 1.00 yards
- Seat: 0.50 yards

MODELS GC3616CA (closed arms)

- Unit: 2.00 yards

Infection Control

- No Velcro on seat
- Seam sealing option
- Zipper sealing option
- Waterfall cleanout between seat and back cushions.
- Metal mesh seat deck. For mental health applications, seat deck can be covered with a solid moisture resistant surface with tamperproof fasteners
- SSU armcaps are cleanable and non-porous
- For proper cleaning and disinfecting practices, the textile selection needs to be identified. It is vital that following any chemical application a clear water wipe down occur to avoid chemical build up that will lead to deterioration of the textile. Contact Global should information on using a specific disinfectant be required

MODELS GC3616CA

- Upholstered arm panels are replaceable

On Site Repair and Replacement

- All components are field replaceable including seat, back, armcaps, and arm frames
- Arm frame are interchangeable allowing for on-site conversion from steel to wood, open arm frames to/from closed arm frames, and single seating to/from ganged seating (ganged seating only available for some models)
- Armcaps are interchangeable allowing for on-site conversion from SSU armcaps to wood armcaps



GC3616



GC3616CEZ
(w/rear casters and lift mechanism)



primacare seating | product specification

Construction (Overall Frame)

- Metal frame with cast zinc connectors and metal-to-metal fasteners
- Arm frames use 14 gauge rectangular tube construction

Construction (Armcaps)

- SSU armcaps
- Armcaps are molded around a formed steel insert ensuring a metal-to-metal connection

Construction (Seat)

- 14 gauge rectangular tube seat frame
- Welded wire mesh seat deck

Construction (Back)

- ¾ in (19 mm) thick molded veneer back, mechanically fastened to back uprights using metal-to-metal connections

Construction (Glides)

- Non-marking, black, polypropylene/polyethylene glides

Upholstery

- Zippered seat cushion
- Seat cushion hooks to underside of seat deck and back rail using proprietary C-clip fastener
- Back cushion hooks to underside of back using proprietary C-clip fastener

Foam

- Seat and back cushions have 3.5 in (89 mm) thick molded urethane foam

Weight Capacity

The weight capacity is 350 lbs.

Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foams and textiles
- 12 year warranty on control mechanisms
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating

All textiles and foam is tested and certified, meeting California Technical Bulletin 117 (CAL 117) standards.

Environmental

View [Environmental Data Sheets](#) online.

All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications.

