primacare seating | product specification

Metal Frame Guest Seating Models GC3620, GC3621, GC3622, GC3623, GC3624, GC3625, GC3626, GC3628 & GC3630

Dimensions

Seat Depth	17.5 in / 445 mm
Seat Height	18 in / 457 mm
Arm Height - From Seat	8.5 in / 216 mm

Single Seat Chairs (Model GC3620)

Overall Depth		27 in / 686 mm
Overall Width		25 in / 635 mm
Overall Height		33 in / 838 mm
Armrest Clearance		20 in / 508 mm
Back Height - From Seat		15 in / 381 mm
Product Weight	GC3620 GC3620CA	54 lbs / 24.5 kgs 64 lbs / 29.1 kgs
Shipping Cube		13.25 ft ³ / 0.37 m ³

Two Seat Chairs (Models GC3621, GC3622 & GC3623)

	,	,
Overall Depth		27 in / 686 mm
Overall Width	GC3621	45 in / 1143 mm
	GC3622 & GC3623	46 in / 1168 mm
Overall Height		33 in / 838 mm
Armrest Clearance	GC3621	40 in / 1016 mm
	GC3622 & GC3623	20 in / 508 mm
Back Height - From Seat		15 in / 381 mm
Product Weight	GC3621	80 lbs / 36.4 kgs
	GC3621CA	88 lbs / 40.0 kgs
	GC3622	86 lbs / 39.1 kgs
	GC3622CA	106 lbs / 48.2 kgs
	GC3623	82 lbs / 37.3 kgs
	GC3623CA	94 lbs / 42.7 kgs
Shipping Cube		45.75 ft ³ / 1.29 m ³

Three Seat Chairs (Models GC3624, GC3625 & GC3626)

Overall Depth		27 in / 686 mm
Overall Width	GC3624	65 in / 1651 mm
	GC3625 & GC3626	69 in / 1753 mm
Overall Height		33 in / 838 mm
Armrest Clearance	GC3624	60 in / 1524 mm
	GC3625 & GC3626	20 in / 508 mm
Back Height - From Seat		15 in / 381 mm
Product Weight	GC3624	114 lbs / 51.8 kgs
	GC3624CA	124 lbs / 56.4 kgs
	GC3625	137 lbs / 62.3 kgs
	GC3625CA	147 lbs / 66.8 kgs
	GC3626	124 lbs / 56.4 kgs
	GC3626CA	134 lbs / 60.9 kgs
Shipping Cube		65.25 ft³ / 1.85 m²

Four and Five Seat Chairs (Models GC3628 & GC3630)

Overall Depth		27 in / 686 mm
Overall Width	GC3628	93 in / 2362 mm
	GC3630	115 in / 2921 mm
Overall Height		33 in / 838 mm
Armrest Clearance		20 in / 508 mm
Back Height - From Seat		15 in / 381 mm
Product Weight	GC3628	172 lbs / 78.2 kgs
	GC3628CA	182 lbs / 82.7 kgs
	GC3630	224 lbs / 101.8 kgs
	GC3630CA	236 lbs / 107.3 kgs
Shipping Cube	GC3628	91.5 ft ³ / 2.59 m ³
	GC3630	111 ft ³ / 3.14 m ³

Contact sales representative for more information.



GC3626CA



primacare seating | product specification

Features

- Wall saver leg design prevents chair back from contact
- Integrated lumbar support
- Standard Self Skinned Urethane (SSU) armcaps
- Complementing tables are available
- Shipped fully assembled

MODELS GC3621 & GC3624

· Connected seats without arms in between MODELS GC3622, GC3625, GC3628 & GC3630

- Full arms and legs between each seat
- · Easy grip forward extending armcaps

MODELS GC3623 & GC3626

- · Armrests only between each seat
- Easy grip forward extending armcaps

Options

- Under arm space is open, as standard, but closed arms are available for all models in matching upholstery (CA models)
- Seven frame finishes are available
- SSU armcaps are available in several colours
- · Optional wood armcaps are available in any standard Globalcare wood finish

MODELS GC3620 & GC3620CA

- Flex back models are available with a torsion control mechanism allowing the back to rock back 14 degrees
- · Wheels can be added to rear wheels for easy rearranging

COM Yardage

Yardage is based on unmatched materials with widths of 54 inches for seating

MODEL GC3620

- Full Unit: 1.75 yards
- Back: 1.00 yards
- Seat: 0.75 yards
- MODEL GC3621
- Full Unit: 3.25 yards
- Back: 2.25 yards
- Seat: 1.00 yards

MODELS GC3622 & GC3623 MODEL GC3630

- Full Unit: 3.25 yards
- Back: 2.00 yards
- Seat: 1.25 yards

MODEL GC3624

- Full Unit: 4.25 yards
- Back: 3.50 yards
- Seat: 0.75 yards

MODELS GC3625 & GC3626

- Full Unit: 4.75 yards
- Back: 3.00 yards
- Seat: 1.75 yards

MODEL GC3628

- Full Unit: 6.00 yards
- Back: 3.75 yards
- Seat: 2.25 yards

- Full Unit: 7.50 yards
- Back: 4.75 yards
- Seat: 2.75 yards

COM Yardage (continued)

MODELS GC36##CA (closed arms)

- GC3620CA Unit: 2.75 yards
- GC3621CA Unit: 3.75 yards
- GC3622CA Unit: 4.50 yards
- GC3623CA Unit: 4.50 yards
- GC3624CA Unit: 5.25 yards
- GC3625CA Unit: 6.25 yards
- GC3626CA Unit: 6.25 yards
- GC3628CA Unit: 8.00 yards
- GC3630CA Unit: 10.00 yards

Infection Control

- No Velcro on seat
- Seam sealing option
- Zipper sealing option
- Waterfall cleanout between seat and back cushions.
- Metal mesh seat deck. For mental health applications, seat deck can be covered with a solid moisture resistant surface with tamperproof fasteners
- SSU armcaps are cleanable and non-porous
- For proper cleaning and disinfecting practices, the textile selection needs to be identified. It is vital that following any chemical application a clear water wipe down occur to avoid chemical build up that will lead to deterioration of the textile. Contact Global should information on using a specific disinfectant be required

MODELS GC3622, GC3625, GC3628 & GC3630

· Upholstered arm panels are replaceable

On Site Repair and Replacement

- · All components are field replaceable including seat, back, armcaps, and arm frames
- Arm frame are interchangeable allowing for on-site conversion from steel to wood, open arm frames to/ from closed arm frames, and single seating to/from ganged seating (ganged seating only available for some models)
- · Armcaps are interchangeable allowing for on-site conversion from SSU armcaps to wood armcaps

Construction (Overall Frame)

- Metal frame with cast zinc connectors and metal-tometal fasteners
- Arm frames use 14 gauge rectangular tube construction

Construction (Armcaps)

- SSU armcaps
- Armcaps are molded around a formed steel insert ensuring a metal-to-metal connection



primacare seating | product specification

Construction (Seat)

- 14 gauge rectangular tube seat frame
- · Welded wire mesh seat deck

Construction (Back)

 0.75 in (19 mm) thick molded veneer back, mechanically fastened to back uprights using metal-tometal connections

Construction (Glides)

• Non-marking, black, polypropylene/polyethylene glides

Upholstery

- Zippered seat cushion
- Seat cushion hooks to underside of seat deck and back rail using proprietary C-clip fastener
- Back cushion hooks to underside of back using proprietary C-clip fastener

Foam

• Seat and back cushions have 3.5 in (89 mm) thick molded urethane foam

Weight Capacity

The weight capacity is 350 lbs.

Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foams and textiles
- 12 year warranty on control mechanisms
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating

All textiles and foam is tested and certified, meeting California Technical Bulletin 117 (CAL 117) standards.

Environmental

View Environmental Data Sheets online.

All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurniture group.com for additional product information including environmental certifications.

