primacare seating | product specification

High Traffic Lounge Seating Models: GC3641, GC3642, GC3643, GC3676, GC3677, GC3678

Dimensions		
_		

Overall Depth	32 in / 813 mm
Overall Height	33 in / 838 mm
Seat Depth	20 in / 508 mm
Seat Height	17.25 in / 438 mm
Back Height	16 in / 406 mm
Arm Height - From Seat	8 in / 203 mm

Single Seat (Model GC3641)

Overall Width Seat Width Armrest Clearance		29 in / 737 mm 23 in / 584 mm 22.7 in / 578 mm			
			Product Weight	GC3641	66 lb / 30.0 kg
				GC3641CA	79 lb / 35.9 kg
Shipping Cube		29.5 ft ³ / 0.83 m ³			

Two Seater (Model GC3642)

Overall Width		52 in / 1321 mm
Seat Width		48 in / 1219 mm
Armrest Clearance		48 in / 1219 mm
Product Weight	GC3642 GC3642CA	107 lb / 48.6 kg 117 lb / 53.2 kg
Shipping Cube		49.5 ft³ / 1.4 m³

Three Seater (Model GC3643)

Overall Width Seat Width Armrest Clearance		75 in / 1905 mm 71 in / 1803 mm 71 in / 1803 mm			
			Product Weight	GC3643 GC3643CA	148 lb / 67.3 kg 158 lb / 71.8 kg
			Shipping Cube		69.5 ft³ / 1.97 m³

Contact sales representative for more information.

Features

- Integrated lumbar support
- Standard Self Skinned Urethane (SSU) armcaps
- Complementing tables are available
- Easy grip forward extending armcaps
- Waterfall clean out
- Metal mesh seat deck
- Wall saver leg design prevents chair back from contact with wall

Options

- Under arm space can be open or closed. Closed arms are available for all models in matching upholstery (CA models)
- SSU armcaps are available in several colors
- Optional wood armcaps and legs are available in any standard Globacare wood finish
- To add sealed seams, contact customer service
- Active fire barrier can be added
- For mental health applications, metal seat deck can be covered in solid moisture resistant surface, secured with tamperproof fasteners

COM Yardage

Yardage is based on unmatched materials with widths of 54 inches for seating

MODEL GC3643

• Full Unit: 6.25 yards

• Back: 5.00 yards

• Seat: 1.25 yards

MODEL GC3641

• Full Unit: 2.50 yards

Back: 1.50 yards

• Seat: 1.00 yards MODEL GC3642

• Full Unit: 4.00 yards

Back: 3.00 yards

• Seat: 1.00 yards

MODELS: GC36##CA (closed arms)

GC3641CA Unit: 3.75 yardsGC3642CA Unit: 5.50 yards

• GC3643CA Unit: 7.50 yards



primacare seating | product specification

Infection Control

- · No Velcro on seat
- · Seam sealing option
- Zipper sealing option
- · Waterfall clean out between seat and back cushions
- Metal mesh seat pan
- SSU arm caps are easily cleanable
- For proper cleaning and disinfecting practices, the
 textile selection needs to be identified. It is vital that
 following any chemical application a clear water wipe
 down occur to avoid chemical build up that will lead
 to deterioration of the textile. Contact Global should
 information on using a specific disinfectant be required

On Site Repair and Replacement

- All components are field replaceable including seat, back, armcaps and arm frames
- Arm frame are interchangeable allowing for on-site conversion from steel to wood, open arm frames to/from closed arm frames, and single seating to/from ganged seating (ganged seating only available for some models)
- Armcaps are interchangeable allowing for on-site conversion from SSU armcaps to wood armcaps

Construction (Overall Frame)

- Metal frame with die-cast zinc connectors and metal-to-metal fasteners
- Arm frames use 14 gauge rectangular tube construction

Construction (Armcaps)

- SSU (Self-Skinned Urethane) armcaps
- Armcaps are molded around a formed steel insert ensuring a metal to metal connection

Construction (Seat)

- 14 gauge rectangular tube seat frame
- · Welded wire mesh seat deck

Construction (Back)

 0.75 in (19 mm) thick molded plywood back, mechanically fastened to back uprights using metal to metal connections

Construction (Glides)

• Non-marking, black, polypropylene/polyethylene glides

Upholstery

- Zippered seat cushion
- Seat cushion hooks to underside of seat deck and back rail using proprietary C-clip fastener
- Back cushion hooks to underside of back using proprietary C-clip fastener

Foam

MODELS: GC3641, GC3642, GC3643

 Seat and back cushions are 6.25 in (159 mm) thick molded urethane foam

MODELS: GC3676, GC3677, GC3678

- Seat cushion is 2 in (51 mm) thick Ultracell foam
- Back cushion is 1.5 in (38 mm) thick molded urethane foam

Weight Capacity

 Designed for an active weight capacity of 500 lb per seat

Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foam and textiles
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating

All textiles and foam is tested and certified, meeting California Technical Bulletin 117 (CAL 117-2013) standards.

Environmental

View Environmental Data Sheets online.

All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including environmental certifications.

