

primacare seating | product specification

High Traffic Patient Seating

Models: GC3631, GC3632, GC3636, GC3655, GC3657

Medium Back Chair Dimensions (Model: GC3631)

Overall Depth	27 in / 686 mm
Overall Width	25 in / 635 mm
Overall Height	36.5 in / 927 mm
Seat Depth	17.5 in / 445 mm
Seat Width	20.5 in / 521 mm
Seat Height	18 in / 457 mm
Back Height - From Seat	18 in / 457 mm
Armrest Clearance	20 in / 508 mm
Arm Height - From Seat	8.5 in / 216 mm
Product Weight	GC3631 56 lbs. / 25.5 kg
	GC3631CA 68 lbs. / 30.9 kg
Shipping Cube	17.5 ft ³ / 0.50 m ³

High Back Chair Dimensions (Models: GC3632, GC3655)

Overall Depth	27 in / 686 mm
Overall Width	25 in / 635 mm
Overall Height	48.5 in / 1232 mm
Seat Depth	17.5 in / 445 mm
Seat Width	20.5 in / 521 mm
Seat Height	18 in / 457 mm
Back Height - From Seat	30 in / 762 mm
Armrest Clearance	20 in / 508 mm
Arm Height - From Seat	8.5 in / 216 mm
Product Weight	GC3632, GC3655 62 lbs. / 28.2 kg
	GC3632CA, GC3655CA 74 lbs. / 33.6 kg
Shipping Cube	27.5 ft ³ / 0.78 m ³

Hip Chair Dimensions (Models: GC3636, GC3657)

Overall Depth	GC3636 26 in / 660 mm
	GC3657 25 in / 635 mm
Overall Width	GC3636 23 in / 584 mm
	GC3657 28 in / 711 mm
Overall Height	GC3636 40.5 in / 1029 mm
	GC3657 41 in / 1041 mm
Seat Depth	17.5 in / 445 mm
Seat Width	GC3636 19 in / 483 mm
	GC3657 24 in / 610 mm
Seat Height	GC3636 25.5 in / 648 mm
	GC3657 26 in / 660 mm
Back Height - From Seat	15.5 in / 394 mm
Armrest Clearance	GC3636 19 in / 483 mm
	GC3657 24 in / 610 mm
Arm Height - From Seat	7 in / 178 mm
Product Weight	GC3636 57 lbs. / 25.9 kg
	GC3657 68 lbs. / 30.9 kg
Shipping Cube	20 ft ³ / 0.57 m ³

Contact sales representative for more information.



GC3631



primacare seating | product specification

Features

- Wall saver leg design prevents chair back from contacting walls before legs contact baseboards
- Integrated lumbar support
- Standard with urethane armcaps
- Complementing tables are available
- Easy grip forward extending armcaps

MODELS: GC3636, GC3657

- Hip chair is designed to assist patients recovering from hip surgery using wider arm clearance, higher seat height and footrest bar

Options

- Metal frame is available in 13 finish colors
- Urethane armcaps are available in several colors
- Optional wood armcaps are available in any standard healthcare wood finish

MODELS: GC3631, GC3632, GC3655

- Flex back models are available with a torsion control mechanism allowing the back rest to rock back 14°
- Wheels can be added to rear wheels for easy rearranging
- Underarm space is open, as standard, but closed arms are available for models in matching upholstery (CA models)

COM Yardage

Yardage is based on unmatched materials with widths of 54 inches for seating

MODEL: GC3631

- Full Unit: 1.75 yards
- Back: 1.00 yards
- Seat: 0.75 yards

MODEL: GC3632

- Full Unit: 2.25 yards
- Back: 1.65 yards
- Seat: 0.60 yards

MODEL: GC3636

- Full Unit: 1.50 yards
- Back: 1.00 yards
- Seat: 0.50 yards

MODELS: GC36##CA (closed arms)

- GC3631CA Unit: 2.75 yards
- GC3632CA Unit: 3.00 yards
- GC3655CA Unit: 3.25 yards

MODEL: GC3655

- Full Unit: 2.50 yards
- Back: 1.50 yards
- Seat: 1.00 yards

MODEL: GC3657

- Full Unit: 1.50 yards
- Back: 1.00 yards
- Seat: 0.50 yards

Infection Control

- No velcro on seat
- Seam sealing option
- Zipper sealing option
- Waterfall cleanout between seat and back cushions
- Metal mesh seat pan
- Urethane armcaps are cleanable and non-porous
- For proper cleaning and disinfecting practices, the textile selection needs to be identified. It is vital that following any chemical application a clear water wipe down occur to avoid chemical build up that will lead to deterioration of the textile. Contact Global should information on using a specific disinfectant be required

On Site Repair and Replacement

- All components are field replaceable including seat, back, armcaps, and arm frames
- Arm frames are interchangeable allowing for on-site conversion from steel to wood, open arm frames to/from closed arm frames, and single seating to/from ganged seating (ganged seating only available for some models)
- Armcaps are interchangeable allowing for on-site conversion from urethane armcaps to wood armcaps

Construction (Overall Frame)

- All connections are metal-to-metal. Primary seat arm connection uses patent pending die-cast zinc connectors
- Arm frames use 14 gauge rectangular tube construction

Construction (Armcaps)

- Urethane armcaps
- Armcaps are molded around a formed steel insert ensuring a metal-to-metal connection

Construction (Seat)

- 14 gauge rectangular tube seat frame
- Welded wire mesh seat deck

Construction (Back)

- 0.75 in (19 mm) thick molded veneer back, mechanically fastened to back uprights using metal-to-metal connections

Construction (Glides)

- Non-marking, black, polypropylene/polyethylene glides



primacare seating | product specification

Upholstery

- Zippered seat cushion
- Seat cushion hooks to underside of seat deck and back rail using proprietary C-clip fastener
- Back cushion hooks to underside of back using proprietary C-clip fastener

Foam

MODELS: GC3631, GC3632, GC3655

- Seat and back cushions have 3.5 in (89 mm) thick molded urethane foam

MODELS: GC3636, GC3657

- Seat cushion is 2.5 in (64 mm) thick Ultracell foam.
Density: 2.6 lbs., ILD: 35
- Back cushion is 2.25 in (57 mm) thick Ultracell foam.
Density: 1.9 lbs., ILD: 22

Weight Capacity

Designed for an active weight capacity is 350 lbs. per seat.

Warranty

Lifetime warranty on all components to the original purchaser except the following:

- 5 year warranty on foam and textiles
- Warranty applies for 24 hours/day, 7 days/week use

Fire Rating

All textiles and foam is tested and certified, meeting California Technical Bulletin 117 (CAL TB 117-2013) standards.

Environmental

View [Environmental Data Sheets](#) online. All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including industry and environmental certifications.

