

# sleep-eez seating | product specification

## Fold-out Sleeper Chairs Model GC3614

### Dimensions (Chair position)

Overall Depth	37 in / 940 mm
Overall Width	34.5 in / 876 mm
Overall Height	34.25 in / 870 mm
Seat Depth	21.5 in / 546 mm
Seat Width	27.5 in / 699 mm
Seat Height	16.5 in / 419 mm
Back Height - From Seat	18 in / 457 mm
Armrest Clearance	27.5 in / 699 mm
Arm Height - From Seat	9.5 in / 241 mm
Product Weight	144 lbs / 71.7 kgs
Shipping Cube	38 ft³ / 1.07 m³

Contact sales representative for more information.

### Features

- Can be operated by one person
- Zero inches of wall clearance required
- Can be used in three functional positions: chair, chaise lounge and sleep surface
- When in sleeping position, provides 24 by 77 in (610 x 1956 mm) sleep surface
- Removable/replaceable seat, back and armcaps
- Shipped fully assembled

### Options

- Armcap options:
  - Wood armcaps are available in all standard wood stain finishes
  - Self Skinned Urethane (SSU) armcaps are available in several colour choices
- Moisture barrier liner can be applied to seat (only) as an option

### COM Yardage

Yardage is based on unmatched materials with widths of 54 inches for seating

- Full Unit: 8.50 yards
- Back: 2.25 yards
- Seat: 6.25 yards

### Infection Control

- Seam sealing option
- Moisture barrier liner option (on seat)
- All components are replaceable on-site
- SSU armcaps are easily cleanable
- For proper cleaning and disinfecting practices, the textile selection needs to be identified. It is vital that following any chemical application a clear water wipe down occur to avoid chemical build up that will lead to deterioration of the textile. Contact Global should information on using a specific disinfectant be required

### Construction (Overall Frame)

- Heavy duty metal frame
- Metal-to-metal connections

### Construction (Armcaps)

- SSU or wood armcaps
- All armcaps are field replaceable



GC3614



# sleep-eez seating | product specification

## Construction (Seat Deck)

- ¾ in (19 mm) thick plywood frame, 6-ply
- Synthetic woven webbing seat suspension system

## Construction (Leg Support)

- Leg support surface is stored in a pull out drawer under the seat. It can be easily brought out and replaced by one person
- ¾ in (19 mm) thick plywood, 6-ply

## Construction (Casters)

- Front two casters do not swivel and may be locked manually
- Back two casters swivel and are non-locking
- 3 in (76 mm) diameter

## Upholstery

- Seat cushion is removable/replaceable
- Front edge of seat is seamless to prevent liquid penetration
- Back cushion is removable/replaceable

## Foam

- Open cell dual density Ultracell urethane foam for enhanced comfort and durability
- Seat and leg cushion foam density:  $2.6 \pm 0.2$  PCF, ILD: 35
- Back cushion foam density:  $1.9 \pm 0.2$  PCF, ILD: 27

## Weight Capacity

Designed for an active weight capacity of 300 lbs.

## Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foam and textiles
- 12 year warranty on control mechanisms
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

## Fire Rating

All fabric and foam is tested and certified, meeting California Technical Bulletin 117 (CAL 117-2013) standards.

## Environmental

View [Environmental Data Sheets](#) online. All foam is produced without using any ozone depleting chloro-flouro chemicals.

## Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

**Please visit [globalfurnituregroup.com](http://globalfurnituregroup.com) for additional product information including environmental certifications.**

