

ml park seating | product specification

Soft Seating

Models ML4634, ML6634 & ML8634

Ottoman

Model ML2634

Seating Dimensions (Models ML4634, ML6634 & ML8634)

Overall Depth		34 in / 864 mm
Overall Width	ML4634	42.75 in / 1086 mm
	ML6634	66 in / 1676 mm
	ML8634	86 in / 2184 mm
Overall Height		32 in / 813 mm
Seat Depth		24 in / 610 mm
Seat Height		20 in / 508 mm
Back Height		12 in / 305 mm
Product Weight	ML4634	85 lbs / 38.6 kg
	ML6634	120 lbs / 54.4 kg
	ML8634	145 lbs / 65.8 kg
Shipping Cube	ML4634	39 ft ³ / 1.10 m ³
	ML6634	41 ft ³ / 1.16 m ³
	ML8634	54 ft ³ / 1.53 m ³

Ottoman Dimensions (Model ML2634)

Overall Depth	26.75 in / 679 mm
Overall Width	26.75 in / 679 mm
Overall Height	18.25 in / 464 mm
Product Weight	35 lbs / 15.9 kg
Shipping Cube	12 ft ³ / 0.34 m ³

Contact sales representative for more information.

Features

- Armless sofas with extended bolsters
- Freestanding
- 6.5 in (165mm) raised legs allow for easy cleaning

Options

- Legs are available in Polished Aluminum, Brushed Aluminium, Black, White or Tungsten finishes
- Can be ordered with a fixed back cushion

MODEL ML4634

- Seamless seat cushion model is available



ML4634



ML2634



ML6634



ML8634

ml park seating | product specification

Construction (Frame)

- Laminated hardwood veneer seat and back frame:
1 in (25 mm) thick, 7-ply
- Synthetic woven webbing seat suspension system

Construction (Legs)

- Die-cast aluminium legs, 1.25 in (32 mm) square profile
- 6.5 in (165 mm) high
- 4 in by 4 in (102 x 102 mm) mounting plate
- Polypropylene non-marking glides

Upholstery (Seat)

- Can be upholstered in fabric, vinyl or leather
- Seat cushions are fixed (non-removable)

Foam (Seat)

- Seat cushion is 5 in (127 mm) thick polyurethane foam
- Density: 4.5 lbs

Foam (Back)

- Back foam is 3 in (76 mm) thick polyurethane foam
- Density: 3.5 lbs

Weight Capacity

Designed for an active weight capacity of 300 lbs per seat

Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foams and fabrics
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating

All fabric and foam is tested and certified, meeting CAL 117 standards.

Environmental

View [Environmental Data Sheets](#) online

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalcontract.com for additional product information including environmental certifications.